






cell type:	NiMH	Conditions
cell size:	AAA	
nominal voltage:	1.2 V	
max. charge voltage:	1.5 V	at standard charge (0.1C / 20°C)
capacity		
nominal:	900 mAh	discharge at 0.2C
minimum:	800 mAh	discharge at 0.2C
	750 mAh	discharge at 1C
		1.0V end discharge voltage
		ta: 20°C
max. continuous discharge current:	2400 mA	ta: 0...45°C
charge		
standard charge:	current 90 mA	time 14....16hrs
quick charge:	250 mA	4hrs
fast charge:	900 mA	1.1hrs
recommended charge termination control parameters:	0...5 mV 0.8...1 °C 45...50 °C	-ΔV (-delta V) temperature rise per minute TCO (temperature cut off)
trickle charge current:	8...25 mA	(recommended)
continuous overcharge: (less than 1 year)	≤ 80 mA	no conspicuous deformation no leakage
internal resistance: (impedance)	≤ 40 mΩ	at 1KHz battery fully charged
life expectancy:	≥ 500 cycles	acc. IEC standard
self discharge		
charge retention:	≥ 80 %	after 12 months storage at 20°C
initial capacity:	≥ 550 mAh	within 30 days after delivery discharge at 0.2C
ambient temperature range:	0...45 °C 10...40 °C - 20...65 °C - 20...50 °C - 20...40 °C - 20...30 °C	standard charge fast charge discharge storage (≤3months) storage (≤6months) storage (≤24months)
QCT1:	20/750/45	
QCT2:	30/700/50	

Diagrams



mechanical specifications

cell dimensions			
diameter d1:		10.5 - 0.7	mm
diameter d2:	max.	3.8	mm
height h1:		44.5 - 1.5	mm
height h2:	min.	0.8	mm
weight:		12.5 ± 2	g



	ANSMANN Specifications for model:	NiMH Battery
		AAA - 900mAh low self discharge
	data sheet no. / part no.	
	supplier no.	702069
	author / date	TG / 01.08.2018